

November 2015

# FEEL-SAFE TECHNICAL APPLICATION GUIDE

## DESCRIPTION

### PERMANENT ANTI-SLIP FLOOR TREATMENT

For use on ceramic, porcelain & natural stone floors & showers  
Improves slip resistance on wet floors  
Long-term slip-fall accident protection

**Universeal Feel Safe** permanent anti-slip treatment uses mild acid solutions to microscopically treat ceramics, porcelain and natural stone to greatly improve slip-resistance on wet floor areas. **Universeal Feel Safe** should not be used on vinyl, linoleum, wood, metal or coated surfaces.

## DIRECTIONS FOR USE

- 1) Make sure surface is free from dirt, grease and oil. Always first test **Universeal Feel Safe** in a small inconspicuous area to determine suitability for intended use. Suitability for a particular purpose is always the responsibility of the user. Apply **Universeal Feel Safe** onto the area to be treated, in small sections. This can be done with a mop, sponge or dry cloth. Agitate wet surface with a stiff brush, let stand for 3-10 minutes. **DO NOT LET SOLUTION DRY ON SURFACE.**
- 2) Reapply if necessary. When each area is completed, thoroughly rinse clean with water and then move onto the next area to be treated. Maximum slip-resistance is attained within 3-10 minutes depending on varying hard mineral surface material.
- 3) **Action time:** 3-10 mins: Ceramic / Porcelain tiles, shower trays & baths 5-10 mins: Natural Stone & Masonry. A test patch must be completed prior to use to determine action time (dwell period) required, as the above times are only a guidance.

**Important:** Always protect areas not to be treated, **Universeal Feel Safe** can cause permanent damage if accidentally spilt or applied on to sensitive surfaces, i.e. metals, painted surfaces, woods, glazed surfaces etc. Always test the product in an inconspicuous area to determine suitability for intended use.

**When properly applied and maintained treated floors will have a slip coefficient exceeding slip-fall safety standards. Universeal will not accept any responsibility for misuse of this product.**

## COVERAGE

Up to 15m<sup>2</sup> per litre.  
DO NOT DILUTE. Must be used neat..

## Usage Guidelines

Dwell Time	Applications/Coats	Application Method	Dilution
3-10 mins	1-2 applications	Mop/Sponge/ Cloth	Undiluted

## PRECAUTIONS

### KEEP OUT OF THE REACH OF CHILDREN & PETS

H314: Causes severe skin burns and eye damage.  
P102: Keep out of reach of children.  
P264: Wash hands thoroughly after handling.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321: Specific treatment (see instructions on this label).  
P405: Store locked up.

Product SDS sheet available to download from the Universeal website.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

