

STONE FOAM TECHNICAL APPLICATION GUIDE

DESCRIPTION

WATER BASED COLOUR ENHANCER

Easy spray-on application No mess foam formula Protects & enhances the colour of natural stone Stain and scuff resistant Up to 15 years protection

Universeal Stone Foam colour enhancer penetrating foam is a low V.O.C. waterbased natural stone colour enhancer that seals and penetrates grout, stone and masonry surfaces to protect against oil and water-based stains. The no $mess\ foam\ formula\ clings\ to\ vertical\ surfaces\ providing\ accurate,\ non-streak$ coverage. Universeal Stone Foam can be applied indoors or outdoors to cured grout, masonry, quarry, saltillo, slate, terracotta, sandstone, brick and precast stone.

DIRECTIONS FOR USE

- Make sure that the surface is dry, thoroughly clean and free from waxes, sealants, or coatings of any kind.
- Shake can well. Point valve opening towards surface to be sprayed, holding about 6-10 inches away. Spray on a fine mist and let stand for a few minutes. Using a clean, dry cloth or sponge, wipe into stone. Repeat if necessary to attain desired look.
- 3) Allow to cure for 24 hours. Test area after application using water droplets, if droplets are absorbed, a second or third coat may be necessary to attain the desired performance.

Please Note: Surfaces which are not to be sealed must be protected with masking material. Always test product in an inconspicuous area to determine suitability for intended use.

Expected wear up to 15 years

This will vary depending on the type of surface, wear and proper maintenance. This is not a warranty.

MAINTENANCE

Clean treated areas with Universeal Easy Clean, do not use harsh or abrasive cleaning agents as this can have a negative effect on the treated surface.

COVERAGE

Coverage per 442ml:

Square metres: 5 to 14m²

Coverage will vary depending on the type of surface application.

Usage Guidelines

Drying Time	Applications/Coats	Application Method	Dilution
20-30 mins	1-3 coats	Cloth	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

Contains: Naptha Petroleum Hydrotreated Light and Butyl Acetate

Extremely flammable aerosol.

Pressurised container: may burst if heated. Causes skin irritation. May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

Precautions:

Hazards:

Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing vapour/spray. Use only outdoors or in a well-ventilated area.

Product SDS sheet available to download from the Universeal website.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

















Universeal Product Agencies Limited

+44 (0)1300 345 898 Fax. +44 (0)844 2480592

Unit 1, Pulham Business Park, Pulham Dorchester DT2 7DX United Kingdom info@universealsealants.co.uk Email: Web: www.universealsealants.co.uk

