

April 2020

PATIO STONE SEALER WET LOOK TECHNICAL APPLICATION GUIDE

UPDATED INSTRUCTIONS AND TECHNICAL GUIDANCE TIPS

Please read carefully in full before applying the product and always complete a test patch to check suitability for your surface. For technical support, please call 01300 345 898 (extension 2).

DESCRIPTION

WET LOOK SEAL FOR NATURAL STONE PAVING, PATIOS & PATHWAYS

Suitable for popular natural stone types including sandstone, Indian sandstone, limestone, slate, quarry tile, travertine, granite & more

Quick drying easy application

Colour enhancing WET LOOK paving sealer finish

Durable, stain-resistant protection

Low odour water based formula

Patio Stone Sealer WET LOOK is a high performance sealer for natural stone paving. Quick drying, creating a durable, colour rich wet look finish for all types of natural porous outdoor flagstones.

Patio Stone Sealer WET LOOK is a water-based polymerised protective coating that creates a highly durable wet look sheen finish on all types of outdoor natural stone. Very easy to apply, it is self levelling and penetrates the substrate to protect against oil and water-based stains.

DIRECTIONS FOR USE

- 1) **Always perform a test in an inconspicuous area on-site to check suitability of product, prior to use - read these instructions fully before application.**
- 2) The surface to be treated must be completely dry and clean. Apply sparingly with a sponge, paint pad, brush or sprayer (**we do not recommend using a roller**). Any excess, puddling or pooling of the sealer must be spread evenly over the surface before allowing to dry (failure to apply correctly may lead to stickiness and/or patches).
- 3) After 60-90 minutes check to see if the first application is dry and ready to receive a second coat. Repeat the process taking care to apply thinly and avoiding puddling / excessive coverage.
- 4) After application it is important that the stone surface is kept completely dry through the curing process, up to 72 hours. Any moisture or water left on the surface within this time may result in the sealer drying inconsistent showing hard to remove white patches.

Please Note: Application range: 5°C – 20°C. In colder conditions the drying time may be extended, do not walk upon or apply further coats until the sealer is completely dry. Always try product in an inconspicuous area prior to use. The wet look finish depends on the number of coats applied. The recommended 2 thin coats will give a darkened, slightly wet & shiny finish. **Do not over apply the product as it may result in moisture issues, leading to stickiness, white patches & blistering/flaking.**


COVERAGE

Apply undiluted, coverage up to 20m²/L per coat.

Coverage will vary depending on surface texture and porosity.

STORAGE INFORMATION

Product shelf life is 12 months from production date (shown on cap) when unopened and stored at room temperature. After opening, use within 3 months.



Usage Guidelines

Drying Time	Applications/Coats	Application Method	Dilution
60-90 mins	1-2 coats	Sponge/ Sprayer/Brush	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H302: Harmful if swallowed.

H319: Causes serious eye irritation.

P102: Keep out of reach of children.

P233: Keep container tightly closed.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash skin thoroughly after handling.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+350: IF ON SKIN: Gently wash with plenty of soap and water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+313: If skin irritation or rash occurs: Get medical advice.



Product SDS sheet available to download from the Universeal website.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

