

April 2020

# GROUT & TILE PROTECTOR TECHNICAL APPLICATION GUIDE

## DESCRIPTION

### INSTANT STAIN PROTECTION

Easy spray-on application  
Can be applied immediately after grouting\*  
Fast drying, instant protection against stains  
Does not change surface appearance

**Universeal Grout & Tile Protector** is a VOC compliant, solvent based formula designed for deep penetration into grout. It protects against oil and water based stains while still allowing the surface to breathe. It is non-yellowing, long lasting and will not change the appearance of the surface. Overspray that does not penetrate the ceramic tile, porcelain, glass, stone or grout will dissipate and not leave any hard to remove residue.

\*Allow grout to harden prior to sealing, typically 1 hour after grouting.

## DIRECTIONS FOR USE

- 1) Before application, make sure the area is well ventilated, ensure you are wearing personal protection equipment including gloves, eye protection and suitable vapour mask.
- 2) Make sure that the surface is thoroughly clean and free from waxes, sealants, or coatings of any kind.
- 3) Shake can well, spray 25–40cm from surface. Apply product evenly, wiping off any excess if spraying on to vertical areas.
- 4) Allow to dry for 1–2 hours and test area after application using water droplets, if droplets are absorbed, a second or third coat may be necessary to attain the desired performance.

**Please Note:** Surfaces which are not to be sealed must be protected with masking material. Do not apply sealer onto acrylic or stained surfaces, such as cabinets, as this may cause discolouration.

### Expected wear up to 20 years

This will vary depending on the type of surface, wear and proper maintenance.

## MAINTENANCE

Clean treated areas with **Universeal Easy Clean**, do not use harsh or abrasive cleaning agents as this can have a negative effect on the treated surface.  
**DO NOT STEAM CLEAN:** steam cleaning will reduce the effectiveness of stain protection and may permanently damage the protective seal.

## COVERAGE

Coverage per 600ml:

Linear feet: Up to 700

Square metres: Up to 15m<sup>2</sup>

## Usage Guidelines

Drying Time	Applications/Coats	Application Method	Dilution
1–2 hours	1–3 coats	Cloth	Undiluted

## PRECAUTIONS

### KEEP OUT OF THE REACH OF CHILDREN & PETS

Contains: Naptha Petroleum Hydrotreated Light and Butyl Acetate

**Hazards:** Extremely flammable aerosol. Pressurised container: may burst if heated. Causes skin irritation.  
May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

**Precautions:** Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing vapour/spray. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required. Get medical advice/attention if you feel unwell.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with national regulations.

Product SDS sheet available to download from the Universeal website.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.



DANGER

