

COLOUR-PLUS TECHNICAL APPLICATION GUIDE

DESCRIPTION

COLOUR ENHANCER FOR ALL OUTDOOR STONE SURFACES For use on all sandstone, granite, limestone and slate patio surfaces Enhances natural colour & texture Helps to prevent staining and heavy soiling Low odour solvent formula

Universeal Colour-Plus is a premium patio and path outdoor impregnating sealer which strongly enhances the natural hues of the stone with deeper, richer, more vibrant colours.

Universeal Colour-Plus is a solvent based colour enhancer and impregnator that penetrates into the surface of the stone to strongly protect from staining and heavy soiling. Universeal Colour-Plus can be applied to grout pointing, tumbled marble, limestone, slate, quarry tiles, sandstone & most types of masonry surfaces. NOT RECOMMENDED FOR USE ON NON-POROUS SURFACES.

DIRECTIONS FOR USE

- 1) Before application the surface must be completely clean and dry, apply an even coat with a low pressure sprayer, natural fibre brush or sponge, any excess sealer must be completely removed from the surface after 20-30 minutes.
- 2) Apply a second application approximately 45-60 minutes repeating the process. After application it is important that the stone surface is kept completely dry through the curing process, up to 72 hours. Any moisture or water left on the surface within this time may result in the sealer drying inconsistent showing hard to remove white patches.

Expected Wear

Under typical conditions the effect of the impregnation can be considered to have an effect for up to 5 years. Effectiveness and longevity is reliant on initial thorough application, foot traffic and the use of correct maintenance cleaning products

Please Note: Areas not to be sealed must be protected with masking materials. It is strongly recommended when using coloured grouts that a stain test is completed before proceeding.

COVERAGE

Up to 25m² per litre per coat. Depending on texture and porosity of surface.

Applications/Coats

1-3

coats

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H226: Flammable liquid and vapour.

H302: Harmful if swallowed

- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H412: Harmful to aquatic life with long lasting effects.

P102: Keep out of reach of children.

P261: Avoid breathing fumes. P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves

P301+330+331: IF SWALLOWED: rinse mouth.

Do NOT induce vomiting. P302+350: IF ON SKIN: Gently wash with plenty of soap and water. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor.

Product SDS sheet available to download from the Universeal website

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

OION



Usage Guidelines

Drying Time

45-60 mins

Universeal Product Agencies Limited

Application Method

Brush/

Sprayer/

Sponge

Unit 1, Pulham Business Park, Pulham Dorchester DT2 7DX United Kingdom +44 (0)1300 345 898 Tel: Email: Fax +44 (0)844 2480592 Web[.]

Dilution

Undiluted

info@universealsealants.co.uk www.universealsealants.co.uk

Colour-Plus



DANGER