

July 2021

# ONE-COAT NANOSEAL TECHNICAL APPLICATION GUIDE

## DESCRIPTION

### INNOVATIVE SOLVENT-BASED STONE IMPREGNATOR

*Unique One-Coat application  
Excellent penetrating properties for polished & dense stone  
Exceptional unrivalled stain protection  
Internal and external use*

**Universeal One-Coat NanoSeal** is a solvent based natural stone patio and path outdoor sealer. Using our unique Micromesh™ premium stain protection to prevent water and dirt from staining the stone surfaces. **Universeal One-Coat NanoSeal** is an innovative solvent based impregnator developed to eliminate the need for more than one coat application to dense natural stone surfaces. Suitable for use with all dense stone surfaces, including polished granites and marbles etc.

## DIRECTIONS FOR USE

- 1) Make sure surface area is completely clean and dry before application. **Universeal One-Coat NanoSeal** is a solvent based liquid and must be used in well-ventilated areas due to its strong solvent smell.
- 2) Shake the product well and apply the sealer generously until saturation of the stone surface. Allow the sealer to stay wet and in contact with the stone surface for at least 5 mins. Apply generously with a low pressure sprayer, natural fibre brush, sponge or paint pad.
- 3) After approximately 15-20 minutes of application, remove any sealer visible on the surface by wiping completely dry with absorbent cloth. If any sealer residue is left on the stone surface wipe clean with a cloth dampened with the solvent sealer.
- 4) Always allow a minimum of 6 hours drying time before grouting, it is recommended that a small test area is done first to check against staining especially when using coloured or polymer modified grouts. In cases with very porous stone it may be necessary to apply more than one application to achieve the desired effect.

### Expected Wear

Under typical conditions the effect of the impregnation can be considered to have an effect for up to 10 years. Effectiveness and longevity is reliant on initial thorough application, foot traffic and the use of correct maintenance cleaning products.

**Please Note:** not applying sealer correctly to saturation of stone may result in inadequate stain protection.

## COVERAGE

Up to 15m<sup>2</sup> per litre per coat.

Depending on texture and porosity of surface.

## Usage Guidelines

Drying Time	Applications/Coats	Application Method	Dilution
15-20 mins	1-2 coats	Sprayer/ Brush/Paint Pad/Sponge	Undiluted

## PRECAUTIONS

### KEEP OUT OF THE REACH OF CHILDREN & PETS

H226: Flammable liquid and vapour.  
H302: Harmful if swallowed.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H412: Harmful to aquatic life with long lasting effects.

P102: Keep out of reach of children.  
P261: Avoid breathing fumes.  
P262: Do not get in eyes, on skin, or on clothing.  
P280: Wear protective gloves.  
P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
P302+350: IF ON SKIN: Gently wash with plenty of soap and water.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor.

Product SDS sheet available to download from the Universeal website.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

