

July 2021

PAVING-PRO SEALER TECHNICAL APPLICATION GUIDE

DESCRIPTION

SUITABLE FOR ALL TYPES OF EXTERNAL BLOCK PAVING

Quick drying easy application
Durable, stain-resistant protection
Delicately enriches natural hues
Low odour water based formula

Universeal Paving-PRO Block Paving Sealer is an outdoor sealer for block paving. Quick drying, the stone surface offers a durable satin finish that helps to prevent soiling and staining.

Universeal Paving-PRO Block Paving Sealer is a water-based polymerised protective coating that creates a durable finish on engineered block paving surfaces. Very easy to apply, it is self levelling and penetrates the substrate to protect against oil and water-based stains.

DIRECTIONS FOR USE


- 1) **Always perform a test in an inconspicuous area on-site to check suitability of product, prior to use - read these instructions fully before application.**
- 2) The paved surface to be treated must be clear of debris, completely dry and ideally recently cleaned.
- 3) Apply thinly with a sponge, paint pad, brush or sprayer (we do not recommend using a roller). The sealer must be applied thinly and evenly, any puddling or pooling of the sealer must be distributed evenly across the surface before allowing to dry.
- 4) After 60-90 minutes check to see if the first application is touch dry and ready to receive a second coat. Repeat the process taking care not to overapply.
- 5) Always allow a minimum of 2-3 hours drying time before limited footfall to ensure maximum long-term protection.

Please Note: Application range: 5°C – 20°C. In colder conditions the drying time may be extended, do not walk upon or apply further coats until the sealer is completely dry. Always perform a test patch in an inconspicuous area on-site prior to use.

PRO-TIP: The amount of satin effect can be controlled by the number of coats applied. The recommended 2 coats will give a soft, subtle sheen finish – add more coats for extra satin effect. Do not over apply the product as it may result in moisture issues, leading to stickiness, white patches & blistering/flaking.

STORAGE INFORMATION

Product shelf life is 12 months from production date (shown on cap) when unopened and stored at room temperature. After opening, use within 3 months.



Usage Guidelines

Drying Time	Applications/Coats	Application Method	Dilution
60 mins	1-2 coats	Sponge/ Brush/Sprayer	Undiluted

COVERAGE

Apply undiluted, coverage range 8-10m²/L per coat.

Coverage will vary depending on surface texture and porosity.

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H302: Harmful if swallowed.
H319: Causes serious eye irritation.
P102: Keep out of reach of children.
P233: Keep container tightly closed.
P262: Do not get in eyes, on skin, or on clothing.
P264: Wash skin thoroughly after handling.
P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P302+350: IF ON SKIN: Gently wash with plenty of soap and water.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+313: If skin irritation or rash occurs: Get medical advice.



Product SDS sheet available to download from the Universeal website.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

