

July 2021

ULTRA WET LOOK SEALER TECHNICAL APPLICATION GUIDE

DESCRIPTION

2 IN 1 SEALER FOR NATURAL STONE SURFACES

Ultimate 2-in-1 sealing power with 100% active low odour solvent breathable formulation - imparts strong water and stain repellency
Suitable for indoor & outdoor uses, including patios, driveways, paths, garages, cladding, façades, floors, worktops, kitchens and more
Minimum 5 Year Performance Guarantee*

1st coat for high intense colour enhancement, 2nd coat for ultimate wet look and high gloss finish
Suitable for all types of porous natural stone: slate, limestone, sandstone, black limestone, plus terracotta, quarry tile, brick, concrete, polished concrete, terrazzo and even grouting and pointing

ULTRA Wet Look Sealer is our ultimate 2-in-1 impregnating formula to boost natural colours & hues and impart a very strong 'wet look' glossy effect.

Universeal's **ULTRA Wet Look Sealer** 100% active, low-odour solvent based sealer offers ultimate protection from staining and soiling whilst offering a greatly enhanced colour boost effect. 2 coats will yield an intense wet look finish that brings out stone's natural hues. Suitable for new patios and also restores faded paving. **NOT RECOMMENDED FOR USE ON NON-POROUS, GLAZED SURFACES SUCH AS CERAMIC OR PORCELAIN TILES.**

DIRECTIONS FOR USE

- Always perform a test in an inconspicuous area on-site to check suitability of product, prior to use - read these instructions fully before application. Before application the surface must be completely clean and dry.**
- To achieve colour enhancement:** Apply a thin, even coat with a low pressure sprayer, paint pad, natural fibre brush or sponge. Any excess sealer must be completely removed from the surface within 15-30 minutes to dry to a flat matt finish.
- For ultimate wet look:** apply a second coat after 60 minutes, with a thin and even application. Leave to dry on the surface (takes up to 12 hours to dry tack free). The end result will be a high gloss, high colour enhanced finish.
- After application it is important the stone surface is kept totally dry through the curing process (minimum 48 hrs). Please check floor is tack free and dry before foot traffic.**

Please Note: Application range: 5°C - 20°C. Areas not to be sealed must be protected with masking materials.

Expected Wear

Under typical conditions, colour protection is guaranteed for 5+ years*. A top-up may be required to maintain gloss finish due to typical footfall and abrasion. Effectiveness and longevity is reliant on correct application and maintenance. *2 coats required for maximum protection.

PRO-TIP: DO NOT OVERAPPLY. Sealer must be applied evenly & thinly. Keep the applied surface area dry for 48hrs to avoid white moisture clouding issues. Please avoid all foot traffic while sealer is still tacky and drying.

COVERAGE

Up to 25m² per litre per coat.

Depending on texture and porosity of surface.

Usage Guidelines

Drying Time	Applications/Coats	Application Method	Dilution
45-60 mins	2 coats recommended	Brush/Sprayer/Sponge	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H226: Flammable liquid and vapour.
H302: Harmful if swallowed.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H412: Harmful to aquatic life with long lasting effects.

P102: Keep out of reach of children.
P261: Avoid breathing fumes.
P262: Do not get in eyes, on skin, or on clothing.
P280: Wear protective gloves.
P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P302+350: IF ON SKIN: Gently wash with plenty of soap and water.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor.



ANGER



Product SDS sheet available to download from the Universeal website.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

CAUTION: BEFORE USE

Please be aware, once this impregnating product has been applied and has cured, the enhancement effect cannot be removed or reversed. Where possible complete a test on off-cuts or some loose sample tiles/stone, failing that ensure the test patch is completed in an isolated, inconspicuous area.

