

February 2022

# PORCELAIN-SEAL TECHNICAL APPLICATION GUIDE

## UPDATED INSTRUCTIONS AND TECHNICAL GUIDANCE TIPS

Please read carefully in full before applying the product and always complete a test patch to check suitability for your surface. For technical support, please call 01300 345 898 (extension 2).

### DESCRIPTION

#### PROTECTIVE SEALER FOR INTERNAL PORCELAIN & CERAMIC TILES

*Excellent on porcelain and ceramic tiling, particularly modern floor tiles  
Enhances colours with a subtle wet look sheen  
Use on walls and floors throughout the home  
Ultra strength sealing for long term protection*

**Universeal Porcelain-Seal** is an innovative, breathable, ultra-durable nano-coating for modern internal porcelain & ceramic wall and floor tiles. It helps to prevent soiling, staining and enhances colours with a subtle sheen.

**Universeal Porcelain-Seal** is a ready to use, quick-drying and easy to apply formula protecting against oil and water-based stains whilst enhancing the finish and leaving an easy to clean surface. **NOT RECOMMENDED FOR USE ON HIGHLY POLISHED SURFACES.**

### DIRECTIONS FOR USE

- 1) Always perform a test in an inconspicuous area on-site to check the suitability of the product, prior to use – read these instructions fully before application.
- 2) Before application make sure the surface is completely dry, clean and free from debris.
- 3) Apply a single coat very thinly and evenly with a micro-fibre cloth, paint pad or flat mop, taking care not to leave application marks or allow the product to puddle on the surface. Aim to achieve a consistent, wet film across the surface of the tiles.
- 4) Allow a minimum of 2 hours drying time before carefully walking onto the sealed surface. For best results, allow 24 hours or more drying before using the treated area.
- 5) Do not proceed with application if the temperature is below 5° C or above 25° C.

**Please Note:** It is imperative that this product is applied correctly, ie thinly and evenly to avoid application marks – this product is designed to be very durable therefore can be very difficult to remove once applied. Refer to direction point 1. For more product information, please refer to our technical datasheet or contact our technical helpline on 01300 345898 ext 2.

### MAINTENANCE

Clean treated areas with **Universeal Easy Clean**, do not use harsh or abrasive cleaning agents as this can have a negative effect on the treated surface.

### COVERAGE

Up to a maximum of 25m<sup>2</sup> per litre per coat

Coverage offered as guidance. Will vary depending on surface porosity, texture and application process.

### Usage Guidelines

Drying Time	Applications/Coats	Application Method	Dilution
2 hours	1 coat	Microfibre Cloth / Paint Pad / Flat Mop	Undiluted

### PRECAUTIONS

#### KEEP OUT OF THE REACH OF CHILDREN & PETS

H302: Harmful if swallowed.

H319: Causes serious eye irritation.

P102: Keep out of reach of children.

P233: Keep container tightly closed.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash skin thoroughly after handling.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+350: IF ON SKIN: Gently wash with plenty of soap and water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+313: If skin irritation or rash occurs: Get medical advice.



Product SDS sheet available to download from the Universeal website.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

### STORAGE INFORMATION

Product shelf life is 12 months from production date (shown on cap) when unopened and stored at room temperature. After opening, use within 3 months.

