

June 2023

RESIN-OFF TECHNICAL APPLICATION GUIDE

DESCRIPTION

ADVANCED FORMULA FOR REMOVING PROBLEMATIC RESIDUES

Designed to remove polymer hazes, films and residues from jointing mortars, resins and surface sealants. Ready to use, gel-like formula

Suitable for porcelain tiles and other porous natural and artificial stones. Highly effective remover - works in less than 20 minutes

Universeal Resin-Off is a specialist stripping formula for the targeted removal of resins and jointing mortar residues from patios and paving. Can also remove excess sealer deposits.

Universeal Resin-Off is for the removal of jointing mortar residues, excess resins and sealants, coatings, adhesives and plastic residues from all types of external stone surfaces. This easy to apply gel-like fluid allows you to target specific patches with minimal mess and wastage.

DIRECTIONS FOR USE

- 1) **Always perform a small test patch on your surface to establish timing and effectiveness of results. ONLY when you have successfully completed this process should you proceed.**
- 2) Prepare the area by cleaning off loose debris and **ENSURE YOU HAVE ADEQUATE PERSONAL PROTECTION, IE GLOVES, SUITABLE PROTECTIVE EYE-WEAR, FACE MASK & CLOTHING.**
- 3) Pre-wet the surface area. Apply Resin-Off to the affected areas and leave to dwell for 15-20 minutes maximum. Agitate with a stiff brush or decking brush and wash off. After rinsing, you may pressure wash for faster results.
- 4) After allowing the surface to dry, inspect and if any stubborn patches remain you may repeat the process.

Please note: do not apply Resin-Off until you have completed a test patch and made sure of the effectiveness and end result on your surface. Cover areas not to be treated with suitable protective materials. Apply between 5° C and 20° C.


Pro-tip: Work in manageable areas of no more than 4-5m² at a time so you can control the dwell time and effectiveness of the break down. Do not apply the product across the entire surface as this will likely lead to an ineffective removal process.

COVERAGE

Apply neat - approximately 5-10m² per litre.

STORAGE INFORMATION

Product shelf life is 12 months from production date (shown on cap) when unopened and stored at room temperature. After opening, use within 3 months. Always shake bottle well before use.



Usage Guidelines

Dwell Time	Applications/Coats	Application Method	Dilution
15-20 mins	1-2 applications	Sponge/ Roller/Brush	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H314: Causes severe skin burns and eye damage.
P102: Keep out of reach of children.
P264: Wash hands thoroughly after handling.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321: Specific treatment (see instructions on this label).
P405: Store locked up.

Product SDS sheet available upon request.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

