

May 2023

## TEMPORARY PROTECTIVE SEALER TECHNICAL APPLICATION GUIDE

### DESCRIPTION

#### SACRIFICIAL COATING FOR EXTERNAL TILING

Water-based temporary protection for porcelain and natural stone paving  
100% protection against cement residues and polymer staining

Protects surface against discolouration when using pigmented grouts  
Sealer is removed by washing off process after grouting

**Universeal Temporary Protective Sealer** is a water-based temporary protection for natural stone and porcelain paving, protects surfaces against discolouration and residues when using cement based pigmented polymerised grouts or pointing systems.

This sacrificial protective coating can be easily removed by washing-off after the completion of grouting or pointing. Temporary Protective Sealer is essential to use when working with modern slurry or brush in pointing paving mortars. When applied correctly it will offer 100% protection against cement residues, pigment and polymer staining.

### DIRECTIONS FOR USE

- 1) Always perform a test in an inconspicuous area on-site to check suitability of product, prior to use - read these instructions fully before application. Before application the surface must be completely clean and dry.**
- 2) Always ensure you have adequate PPE and suitable protective clothing. All application tools can be washed with warm clean water after use and before drying.**
3. Ensure paving surfaces are clean, dry and free from contamination.
4. Shake container well before use. Apply the Temporary Protective Sealer thoroughly with roller, brush, sponge or micro fibre cloth.
5. Rub well into the surface but avoid application to un-grouted joints.
6. Allow 15-20 minutes for first coat to surface dry before applying the second application.
7. Apply the second application in the same way as the first, allow to dry for a minimum 1 hour, (longer in cold temperatures) before proceeding with the application of the grout or pointing system.
8. During washing-off process, Temporary Protective Sealer will be removed. Any residual can be removed with clean water after the grouting or pointing has set.

**Please note: do not use in temperatures below 5°C or in damp conditions. Use undiluted, apply before grouting or pointing begins.** Cover areas not to be treated with suitable protective materials. Apply between 5° C and 20° C.

### COVERAGE

Approximately 10-12m<sup>2</sup> per litre for 2 coat application.  
Coverage offered as guidance. Will vary depending on surface porosity, texture and application process.

### Usage Guidelines

Drying Time	Applications/Coats	Application Method	Dilution
15-20 mins (1st coat) 1+ hours (2nd coat)	2 coats recommended	Brush/Roller/ Sponge/Cloth	Undiluted

### PRECAUTIONS

#### KEEP OUT OF THE REACH OF CHILDREN & PETS

- H302: Harmful if swallowed.  
H319: Causes serious eye irritation.  
P102: Keep out of reach of children.  
P233: Keep container tightly closed.  
P262: Do not get in eyes, on skin, or on clothing.  
P264: Wash skin thoroughly after handling.  
P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
P302+350: IF ON SKIN: Gently wash with plenty of soap and water.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333+313: If skin irritation or rash occurs: Get medical advice.



Product SDS sheet available upon request.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

