

July 2023

HYDROSEAL TECHNICAL APPLICATION GUIDE

DESCRIPTION

WATER BASED STONE & MASONRY IMPREGNATOR SEALER

For use on all types of natural stone & masonry surfaces

Suitable for interior & exterior use

Does not alter the natural look

Environmentally friendly

Universeal Hydroseal is a water based stone and masonry impregnator that penetrates into the surface to protect against oil and water based stains whilst leaving a matt unchanged finish. **Universeal Hydroseal** can be used for internal and external application, suitable for the application to all porous textured stone and masonry surfaces. **NOT RECOMMENDED FOR USE ON HIGHLY POLISHED, CERAMIC/GLAZED, DENSE OR NON-POROUS SURFACES.**

DIRECTIONS FOR USE

- 1) Before application the surface must be completely clean and dry.
- 2) Apply generously and evenly with a low pressure sprayer, natural fibre brush or sponge (we do not recommend using a roller).
- 3) Apply a second application approximately 20-30 minutes after the first whilst the stone surface is still showing slightly damp inside. It will take at least 24 hours before the product will offer full protection. Until this has happened, keep the surface free from water and oil spills, as stains may occur before fully cured.

Please Note: Areas not to be sealed with Hydroseal Stone Sealer must be protected with masking materials. It is strongly recommended when using coloured grouts that a stain test is completed before proceeding. Some materials may appear slightly darker after treatment. **If no prior product experience exists or in cases of doubt, we recommend a trial application.** Always treat the entire surface in a room. This product does not protect against acid ingress. Remove splashes on wood, glass, PVC, lacquered surfaces etc with a damp cloth.

Application Temperature: the temperature of the surface should be between 5°C and 25°C. Switch off under floor heating prior to application.

COVERAGE

Up to 30m² per litre

This will depend on the porosity of surface. Check the surface after application to ensure full effectiveness of impregnator. Apply a second or third coat if necessary.

MAINTENANCE

Clean treated areas with **Universeal Easy Clean**, do not use harsh or abrasive cleaning agents as this can have a negative effect on the treated surface.

Usage Guidelines

Drying Time	Applications/Coats	Application Method	Dilution
45-60 mins	1-2 coats	Brush/Sprayer/ Sponge/Paint Pad	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H302: Harmful if swallowed.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

P102: Keep out of reach of children.

P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce

vomiting. P302+350: IF ON SKIN: Gently wash with plenty of soap

and water. P305+351+338: IF IN EYES: Rinse cautiously with water

for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. P309+311: IF exposed or if you feel unwell: Call

a POISON CENTRE or doctor. P332+313: If skin irritation occurs: Get medical

advice. P337+313: If eye irritation persists: Get medical advice.



Product SDS sheet available upon request.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.

STORAGE INFORMATION

Product shelf life is 12 months from production date (shown on cap) when unopened and stored at room temperature. After opening, use within 3 months.

