SEALERS · CLEANERS · MAINTENANCE · OUTDOORS ADVANCED TECHNOLOGY FOR TILE & STONE SURFACES

PATIO STONE SEALER COLOUR ENHANCED TECHNICAL APPLICATION GUIDE

UPDATED INSTRUCTIONS AND TECHNICAL GUIDANCE TIPS

Please read carefully in full before applying the product and always complete a test patch to check suitabliliy for your surface. For technical support, please call 01300 345 898 (extension 2).

DESCRIPTION

COLOUR ENHANCER FOR NATURAL STONE PAVING, PATIOS & PATHWAYS

Suitable for popular natural stone types including sandstone, limestone, slate, quarry tile, travertine, granite & more Suitable for use on concrete and precast paving Quick drying easy application

100% breathable allowing for vapour transmission LOW SHEEN COLOUR PLUS finish Durable, stain-resistant protection Low odour water based formula

Patio Stone Sealer COLOUR ENHANCED is the ideal outdoor sealer for paving, patio & paths. Quick drying, the natural stone colours will be highly enhanced with a very durable matt finish. The advanced polymerised formula is 100% breathable allows full vapour transmission to avoid moisture issues. Patio Stone Sealer COLOUR ENHANCED is a water-based impregnating sealer that creates a longlasting colour enhanced finish on all types of outdoor porous natural stone. Very

easy to apply, it fully penetrates the stone to protect against water stains, organic soiling and algae growth.

DIRECTIONS FOR USE

- Always perform a test in an inconspicuous area on-site to check suitability of product, prior to use - read these instructions fully before application.
- Shake bottle well before use. Before application the surface must be completely clean and dry, apply a light and even coat of Patio Stone Sealer COLOUR ENHANCED with a low pressure sprayer, natural fibre brush or sponge (we do not recommend using a roller). DO NOT OVERAPPLY: any excess sealer must be completely removed from the surface after 20-30 minutes, failure to remove
- the excess will lead to an unwelcome tacky, shiny finish and/or patchiness. Apply a second application approximately 45-60 minutes repeating the process. After application it is important that the stone surface is kept completely dry through the curing process, up to 72 hours. Any moisture or water left on the surface within this time may result in the sealer drying inconsistent showing hard to remove white patches

Please Note: Application range: 5°c - 20°c. Areas not to be sealed must be protected with masking materials. Always shake bottle well before use. Results may vary when applying COLOUR ENHANCED FINISH, depending on the colour, texture and condition of your natural stone. As a rule, it does not provide radical transformational effects when applied to lighter stones, and in particular, it cannot enhance common light and grey sandstones such as Kandla Grey or any mixed colour blend containing light greys as it may dry inconsistent and patchy in colour. The sealer will always deliver more noticeable results on darker or colour infused stones, so if you are unsure, we would recommend you complete a test patch first to see how the finish works on your patio area.

COVERAGE

Apply undiluted, coverage up to 25m2/L per coat.

Coverage will vary depending on surface texture and porosity.

STORAGE INFORMATION

Product shelf life is 12 months from production date (shown on cap) when unopened and stored at room temperature. After opening, use within 3 months. Always shake bottle well before use.





Usage Guidelines

Drying Time	Applications/Coats	Application Method	Dilution
45-60 mins	1-2 coats	Sponge/ Sprayer/Brush	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H302: Harmful if swallowed H319: Causes serious eye irritation.

P102: Keep out of reach of children.

P233: Keep container tightly closed.

P262: Do not get in eyes, on skin, or on clothing. P264: Wash skin thoroughly after handling.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+350: IF ON SKIN: Gently wash with plenty of soap and water. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P333+313: If skin irritation or rash occurs: Get medical advice.

Product SDS sheet available to download from the Universeal website.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.





Universeal Product Agencies Limited

Units 1 & 4, Pulham Business Park, Pulham Dorchester DT2 7DX United Kingdom +44 (0)1300 345 898 Email: info@universealsealants.co.uk Fax. +44 (0)844 2480592 Web: www.universealsealants.co.uk

