

# **STAIN-GUARD TECHNICAL APPLICATION GUIDE**

#### DESCRIPTION

NATURAL FINISH STONE SEALER Professional stain protection Suitable for interior & exterior use Protects against oil & water stains Low odour solvent formula

Universeal Stain Guard Matt Stone is a solvent-based natural stone impregnator that penetrates into the surface to protect against oil and water based stains.

Universeal Stain-Guard Matt Stone can be used for internal and external application, suitable for the application to all porous textured stone and masonry surfaces.

# **DIRECTIONS FOR USE**

- 1) Before application make sure the surface is completely dry, clean and free from debris.
- 2) Generously apply with a low pressure sprayer, paint pad, brush or sponge (we do not recommend using a roller). Remove any excess sealer from the stone surface after 20-30 minutes
- 3) Apply a second application approximately 45-60 minutes after the first application repeating the process. It will take at least 24 hours before the product will offer full protection. Until this has happened, keep the surface free from water and oil spills, as stains may occur before fully cured.

Please Note: Areas not to be sealed must be protected with masking materials. It is strongly recommended when using coloured grouts that a stain test is completed before proceeding.

#### **EXPECTED WEAR UP TO 20 YEARS**

Varies depending on the type of surface, wear and correct maintenance procedures.

## MAINTENANCE

Clean treated areas with Universeal Easy Clean, do not use harsh or abrasive cleaning agents as this can have a negative effect on the treated surface.

## COVERAGE

Up to 30m<sup>2</sup> per litre per coat

This will depend on the porosity of surface. Check the surface after application to ensure full effectiveness of impregnator.

## **Usage Guidelines**

Drying Time	Applications/Coats	Application Method	Dilution
45-60 mins	1-2 coats	Brush/Sprayer/ Sponge	Undiluted

# PRECAUTIONS

#### **KEEP OUT OF THE REACH OF CHILDREN & PETS**

H226: Flammable liquid and vapour.

H302: Harmful if swallowed

- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H412: Harmful to aquatic life with long lasting effects.

P102: Keep out of reach of children.

P261: Avoid breathing fumes. P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P302+350: IF ON SKIN: Gently wash with plenty of soap and water. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor.

#### Product SDS sheet available upon request.

This information is offered without guarantee. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. In case of doubt, the product should be tried out in an inconspicuous area. In the event of failure, the manufacturer shall be obliged to replace such product proven defective.





#### **Universeal Product Agencies Limited**

+44 (0)1300 345 898 Tel: Fax +44 (0)844 2480592

Units 1 & 4, Pulham Business Park, Pulham Dorchester DT2 7DX United Kingdom Email: info@universealsealants.co.uk Web<sup>.</sup> www.universealsealants.co.uk



ARNING